

FORMOST FUJI

FUJI-FORMOST FW-3400MS WRAPPER

Quality is "First and Formost"



HIGH-SPEED OPERATION

TIGHT, ATTRACTIVE PACKAGES

CANTILEVERED FRAME

REPEATABLE SETTINGS

FAST CHANGEOVERS

DESIGNED FOR SHRINK FILM WRAPPING

Based on the FW-3400 Horizontal Servo Wrapper, the FW-3400MS Shrink Wrapper utilizes a melt-cut-sealer for both the center and end seals so that high strength seals can be achieved. The wrapped product then passes through a heat tunnel creating a clean, tight package.

The Model FW-3430MS/B Box Motion Shrink Wrapper is configured to wrap the film around the package so that the seals are located along three horizontal sides of the package to allow maximum surface availability of the package for distortion free graphics. A box motion melt-cut-sealer is used for the three side seals. The Model FW-3430MS/B is ideal for CD jewel cases, DVD cases or videotape cases.

FORMOST FUJI CORPORATION

19211 144th Avenue NE • Woodinville, WA 98072

Phone: 425-483-9090 • Fax: 425-486-5656 • email: salesoffice@formostfuji.com

www.formostfuji.com

FUJI-FORMOST FW-3400MS WRAPPER

FW-3400MS

Shrink Film Wrapper

- Wraps rectangular or cylindrical shaped products
- Trimmed seals and tight, attractive package
- Up to 300 ppm



FW-3410MS

Shrink Film Wrapper

- Designed for larger products
- Up to 150 ppm



FW-3430MS/B

Shrink Film Wrapper

- Box motion end sealers
- Ideal for low profile products like CD and DVD cases and videotape cases
- Up to 100 ppm



FW-3400MS/VK & FW-3410MS/VK

Shrink Film Wrappers

- Equipped with vertical rotary end sealers
- Designed for shrink wrapping multipacks of column or cubic products
- Up to 300 ppm



Optional Features

Automation, Integration

Automated feed systems and full line integration capabilities.

Packless Function

When no product is present, no package is made.

Cutless Function

When product is sensed out of time at the end sealers, the sealers are stopped in the open position and remain open until product is clear and no jam occurs.

Automatic Film Splicer

Designed for registered printed film.

SPECIFICATIONS

Machine Model		FW-3400MS
Operating Speed		10-300 packs/min
Product Dimensions	Width	5 1/2" Max.
	Height	2 3/8" Max.

Machine Model		FW-3410MS
Operating Speed		10-150 packs/min
Product Dimensions	Width	7 7/8" Max.
	Height	3 15/16" Max.

Machine Model		FW-3430MS/B
Operating Speed		10-100 packs/min
Product Dimensions	Width	5 11/16" Max.
	Height	1 1/4" Max.

Machine Model		FW-3400MS/VK
Operating Speed		10-300 packs/min
Product Dimensions	Width	2 3/8" Max.
	Height	5 1/2" Max.

Machine Model		FW-3410MS/VK
Operating Speed		10-150 packs/min
Product Dimensions	Width	3 15/16" Max.
	Height	7 7/8" Max.

Specifications may vary according to application, and the right is reserved to make changes without notice.

FORMOST FUJI CORPORATION

19211 144th Avenue NE • Woodinville, WA 98072

Phone: 425-483-9090 • Fax: 425-486-5656 • email: salesoffice@formostfuji.com

www.formostfuji.com